
CABLE REEL STAND COMBO

4-Way Forklift Pickup With Removable Wheels



CABLE REEL STAND COMBO

4-Way Forklift Pickup With Removable Wheels

The Reel-O-Matic Combo is constructed of all tubular welded steel. Our stands are complete with a 2" diameter solid steel shaft, cam roller bearings that allow for easy reel payout, shaft safety locks with locking pin and a maximum reel weight of 5,000 lbs. Load the reel(s) at your facility and deliver right to the job-site.

Popular Reel Configurations							
8x	RPR-15-14	Single Compartment Reel Measuring	40" OD x 16" ID x 4" W				
4x	RPR-15	Single Compartment Reel Measuring	40" OD x 16" ID x 8" W				
5x	RPR-15-01	Single Compartment Reel Measuring	40" OD x 16" ID x 6" W				
1x	RPR-25	Two Compartment Reel Measuring	40" OD x 16" ID x 32" W				
1x 1x	RPR-35-001 RPR-15	Three Compartment Reel Measuring Single Compartment Reel Measuring	40" OD x 16" ID x 24" W 40" OD x 16" ID x 8" W				
1x	RPR-45	Three Compartment Reel Measuring	40" OD x 16" ID x 32" W				
1x 1x	RPR-45-01 RPR-15-01	Four Compartment Reel Measuring Single Compartment Reel Measuring	40" OD x 16" ID x 26" W 40" OD x 16" ID x 6" W				
1x	RPR-55	Five Compartment Reel Measuring	40" OD x 16" ID x 32" W				
4x	RPR-15-06	Single Compartment Reel Measuring	48" OD x 16" ID x 8" W				
5x	RPR-15-08	Single Compartment Reel Measuring	48" OD x 16" ID x 6" W				
1x 1x	RPR-35-004 RPR-15-06	Four Compartment Reel Measuring Single Compartment Reel Measuring	48" OD x 16" ID x 24" W 48" OD x 16" ID x 8" W				
1x	RPR-35-007	Three Compartment Reel Measuring	48" OD x 16" ID x 32" W				
1x 1x	RPR-45-04 RPR-15-08	Four Compartment Reel Measuring Single Compartment Reel Measuring	48" OD x 16" ID x 26" W 48" OD x 16" ID x 6" W				
1x	RPR-48-07	Four Compartment Reel Measuring	48" OD x 16" ID x 32" W				
1x	RPR-55-06	Five Compartment Reel Measuring	48" OD x 16" ID x 32" W				

Approximate Reel Capacity Chart							
THHN		RPR - 15	RPR - 15	RPR - 45	RPR - 45		
Wire Size	OD in Inches	40" Diameter	48" Diameter	40" Diameter	48" Diameter		
750 MCM	1.16"	341′	358′	341′	448′		
600 MCM	1.06"	409′	437′	409′	546′		
500 MCM	0.925"	537′	592′	537′	740′		
400 MCM	0.842"	665′	715′	665′	894′		
350 MCM	0.796"	716′	798′	716′	998′		
300 MCM	0.747"	806′	904′	806′	1130′		
250 MCM	0.694"	979′	1048′	979′	1310′		
4/0	0.624"	1152′	1238′	1152′	1547′		
3/0	0.568"	1478′	1494′	1478′	1867′		
2/0	0.518"	1913′	1796′	1913′	2245′		
1/0	0.474"	2150′	2145′	2150′	2681′		



Removable 8" x 2" Polyurethane Wheels



Standard 2 1/8" Locking Reel Collar



Standard Shaft Safety Locks

