REEL ROLLER PLATFORMS

Easy Pay-Out From Any Reel

Tough Structural Steel Frame and Front Roller Locks to Ease Reel Removal. Side Rollers are Included. Low Base Design to Avoid Damaging of Cable Inside Reel. Rugged Steel "Angle" Construction with Steel Plate Ramp.



Model 280S, 300S, and 380S



The Leader in Reeling, Coiling & Processing Solutions

6408 S. Eastern Avenue | Oklahoma City, OK. 73149 405.672.0000 | 405.672.7200 Fax www.reelomatic.com

REEL ROLLER PLATFORMS

Easy Pay-Out From Any Reel

Standard Features

- Front Roller Lock for Ease of Reel Removal
- Side Roller Bearings to Prevent Reel Flange Chafing
- Raised Rear Roller to Help Secure the Reel in Place
- Adjustable Roller to Handle Reels from 24" to 60" Diameter



Model 600 Adjustable Reel Roller Platform

Standard Sizes Available:

- 280S 28" Wide X 2,000 LBS
- 300S 30" Wide X 2,000 LBS
- 360S 36" Wide X 2,000 LBS
- 480DW HD 48" Wide X 2000 LBS (Per Side)
- 600 Adjustable Width X 3,000LBS

Powered Reel Roller Platforms Available. Consult Us About Your Platform Needs



480 DW - 48" Wide * Two Reels - 24" Wide



HDRR5 5,000 LB High Capacity Unit



The Leader in Reeling, Coiling & Processing Solutions

6408 S. Eastern Avenue | Oklahoma City, OK. 73149 405.672.0000 | 405.672.7200 Fax www.reelomatic.com