
## **CRS/RPR COMBO**

## CRS-48-035, (5) RPR-15-01

Independently free spinning Single Compartment Reels



Combo Paralleling Cable Reel Stand with five (5) independent free-spinning RPR 15 paralleling reels measuring 40" O.D. x 16" I.D. x 6" wide. Includes 2" O.D. shaft with locking collars and safety latches. Also includes forklift base bar.



6408 S. Eastern Avenue | Oklahoma City, OK. 73149 405.672.0000 | 405.672.7200 Fax www.reelomatic.com

The Leader in Reeling, Coiling & Processing Solutions

## CABLE REEL STAND COMBO

## Forklift Pickup

The Reel-O-Matic Combo is constructed of all tubular welded steel. Our stands are complete with a 2" diameter solid steel shaft, cam roller bearings that allow for easy reel payout, shaft safety locks with locking pin and a maximum reel weight of 5,000 lbs. Load the reel(s) at your facility and deliver right to the job-site.

Popular Reel Configurations							
8x	RPR-15-14	Single Compartment Reel Measuring	40" OD x 16" ID x 4" W				
4x	RPR-15	Single Compartment Reel Measuring	40" OD x 16" ID x 8" W				
5x	RPR-15-01	Single Compartment Reel Measuring	40" OD x 16" ID x 6" W				
1x	RPR-25	Two Compartment Reel Measuring	40" OD x 16" ID x 32" W				
1x 1x	RPR-35-002 RPR-15	Three Compartment Reel Measuring Single Compartment Reel Measuring	40" OD x 16" ID x 24" W 40" OD x 16" ID x 8" W				
1x	RPR-45	Three Compartment Reel Measuring	40" OD x 16" ID x 32" W				
1x 1x	RPR-45-01 RPR-15-01	Four Compartment Reel Measuring Single Compartment Reel Measuring	<b>40" OD</b> x 16" ID x 26" W <b>40" OD</b> x 16" ID x 6" W				
1x	RPR-55	Five Compartment Reel Measuring	40" OD x 16" ID x 32" W				
4x	RPR-15-06	Single Compartment Reel Measuring	48" OD x 16" ID x 8" W				
5x	RPR-15-08	Single Compartment Reel Measuring	48" OD x 16" ID x 6" W				
1x 1x	RPR-35-004 RPR-15-06	Four Compartment Reel Measuring Single Compartment Reel Measuring	48" OD x 16" ID x 24" W 48" OD x 16" ID x 8" W				
1x	RPR-35-007	Three Compartment Reel Measuring	48" OD x 16" ID x 32" W				
1x 1x	RPR-45-04 RPR-15-08	Four Compartment Reel Measuring Single Compartment Reel Measuring	<b>48" OD</b> x 16" ID x 26" W <b>48" OD</b> x 16" ID x 6" W				
1x	RPR-48-07	Four Compartment Reel Measuring	48" OD x 16" ID x 32" W				
1x	RPR-55-06	Five Compartment Reel Measuring	48" OD x 16" ID x 32" W				

Ĩ				1
			~	K
3				
	0	L		
		C		

Standard 2 1/8" Locking Reel Collar

Approximate Reel Capacity Chart								
THHN		RPR - 15	RPR - 15	RPR - 45	RPR - 45			
Wire Size	OD in Inches	40" Diameter	48" Diameter	40" Diameter	48" Diameter			
750 MCM	1.16″	341′	358′	341′	448'			
600 MCM	1.06″	409′	437'	409'	546′			
500 MCM	0.925″	537′	592'	537'	740'			
400 MCM	0.842″	665′	715′	665′	894'			
350 MCM	0.796″	716′	798′	716′	998'			
300 MCM	0.747″	806′	904′	806′	1130'			
250 MCM	0.694″	979′	1048′	979′	1310′			
4/0	0.624″	1152′	1238′	1152′	1547′			
3/0	0.568″	1478′	1494′	1478′	1867′			
2/0	0.518″	1913′	1796′	1913′	2245′			
1/0	0.474″	2150'	2145′	2150′	2681′			



Standard Shaft Safety Locks



The Leader in Reeling, Coiling & Processing Solutions

6408 S. Eastern Avenue | Oklahoma City, OK. 73149 405.672.0000 | 405.672.7200 Fax www.reelomatic.com