

# CABLE REEL RACK

The Best Cable Reel Rack Solution!



- Can be assembled quickly by one person.
- Easy to disassemble and relocate.
- Handles heavy loads.
- May be extended in width for larger applications.
- Enables fast changing of materials.
- Each axle can handle up to 2,000 lbs.
- Cable Reel Rack uses U.S. grade high strength steel.
- Maximum diameter axle bracket will hold is 1.75" diameter axle.

*\* Axles Not Included, Must Order Separately*

# CABLE REEL RACK

The Best Cable Reel Rack Solution!

## STANDARD STARTER UNITS

Part Number	Width	Depth	Height	Weight
CR4824096	48"	24"	96"	128.27 lbs
CR4836096	48"	36"	96"	132.66 lbs
CR4836120	48"	36"	120"	166.44 lbs

Green Uprights & Orange Beams

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>■ <b>10,000lb. Capacity + 8' Units Include:</b> <ul style="list-style-type: none"> <li>• 2 Uprights</li> <li>• 3 Tie Beams</li> <li>• 3 Sets of Axle Brackets</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li>■ <b>10' &amp; 12' Units Include</b> <ul style="list-style-type: none"> <li>• 2 Uprights</li> <li>• 4 Tie Beams</li> <li>• 4 Sets of Axle Brackets.</li> </ul> </li> </ul> |
|---|---|



Snap-In Crossmembers

## STANDARD ADDER UNITS

Part Number	Width	Depth	Height	Weight
CR4824096	48"	24"	96"	86.86 lbs
CR4836096	48"	36"	96"	89.05 lbs
CR4836120	48"	36"	120"	113.52 lbs

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>■ <b>10,000lb. Capacity + 8' Units Include:</b> <ul style="list-style-type: none"> <li>• 1 Upright</li> <li>• 3 Tie Beams</li> <li>• 3 Sets of Axle Brackets</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li>■ <b>10' &amp; 12' Units Include</b> <ul style="list-style-type: none"> <li>• 1 Upright</li> <li>• 4 Tie Beams</li> <li>• 4 Sets of Axle Brackets.</li> </ul> </li> </ul> |
|--|--|



Easy Axle Installation

## AXLE BRACKETS

Part Number	Capacity	Weight
14500	2,000 / Pair	2,296 lbs / Pair

The width dimensions between columns - not the axle brackets. Cut size for the actual axle is 1/2" less than actual width needed. Example (24" wide unit needs 23 1/2" axle.)