GANTRY TAKE UPS & PAYOFFS

GTU Series 2.5 to 15 Ton

GTU/GPO

Gantry Take-Up & Payoffs

Traversing Frame Take-Ups and Payoffs are some of the most advanced on the market today, now with capacities up to 100,000 pounds. These units offer such benefits as: true walk-thru capability and unlimited lateral movement for reel handling. The units traverse the entire reel in front of the line, creating an optimum layer wound package. The telescoping portal design conforms to the size of reel to minimize floor space requirements. Main drive systems are engineered to customers' specifications and are complemented with operator Touchscreen Interface.



Overhead beam units are also available.

Equipment Benefits

Zero Material Fleeting Angle

- Superior level-wind capabilities.
- Tandem operation allows for continuous line operation and offers faster and more convenient loading.
- Minimized line lengths even with large, non-flexible material.
- Processes round, flat and rectangular products

Superior Controls

- Standard controls fit all applications of dancer, speed, or torque controls with selectable diameter and line speed compensation.
- Color touchscreen on take-up and payoff allows complete operator control and maintenance access
- Independent load control stations for convenient load access

Telescoping Frame Conforms to the Actual Reel Size

- Offers true roll thru capabilities
- Increased productivity
- Improved bolt-on arbor cone design

Optional

- Rim Driven Systems
- Overhead beam design
- Auto reel loading
- Zero fleeting angle payoffs
- Integrated Safty Scanner



GANTRY TAKE UPS & PAYOFFS

GTU Series 2.5 to 15 Ton

Standard	Models	and	Specifications
----------	--------	-----	----------------

MODEL	Flange Diameter MIN / MAX in(mm)	Outside Width MIN / MAX in(mm)	Weight Capacity T/lbs
GTU/GPO-5	28 (711) / 72 (1,829)	24 (610) / 48 (1,219)	2.5 / 5,000
GTU/GPO-10	30 (762) / 96 (2,438)	30 (762) / 54 (1,372)	5 / 10,000
GTU/GPO-15	36 (915) / 96 (2,438)	36 (915) / 67 (1,702)	7.5 / 15,000
GTU/GPO-20	36 (915) / 96 (2,438)	36 (915) / 67 (1,702)	10 / 20,000
GTU/GPO-30	36 (915) / 96 (2,438)	36 (915) / 67 (1,702)	15 / 30,000



GTU-30 115 Inch Cap







GTU-10A-with Panelview



Hardened Arbor Adapters



Protective Cable Tracks



Protective Cable Tracks



Guarded Contol Panel

